

TUFOOD® FAT 16 2SP



TECHNICAL CHARACTERISTICS

Temperature range : -25°C / +80°C (-13°F / +176°F)

Norms : ISO 1307 for dimensional tolerances



Suction and delivery hose suitable for fatty and non-fatty food products.

DESCRIPTION

Tube

NBR, white, phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.2600, BFR recommendation XXI cat 2, DM 21.03.73 e seguenti, EUROPEAN REGLEMENT 1935/2004/CE, JAPAN-Ministry of Health and Welfare Notice No.370,1959 and No.201,2006, 3A Sanitary Standard Class II

Reinforcement

synthetic plies, galvanized wire helices

Cover

smooth, blue, abrasion, ageing, ozone and oil resistant, cloth finish

Inside diameter		Outside diameter		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	[in]	[mm]	[in]	[bar]	[psi]	[bar]	[psi]	[bar]	[psi]	[kg/mt]	[lbs/ft]	[mm]	[in]
19	0,75	31	1,22	0,9	13	16	250	48	750	0,71	0,48	60	2,36
25	0,98	37	1,46	0,9	13	16	250	48	750	0,87	0,58	85	3,35
38	1,50	51	2,01	0,9	13	16	250	48	750	1,39	0,93	150	5,91
50	1,97	64	2,52	0,9	13	16	250	48	750	1,81	1,22	210	8,27
63,5	2,50	78	3,07	0,9	13	16	250	48	750	2,52	1,69	265	10,43
75	2,95	90	3,54	0,9	13	16	250	48	750	2,92	1,96	320	12,60
102	4,00	122	4,80	0,9	13	16	250	48	750	5,51	3,70	435	17,13

Data refer to ambient temperature (20°C). Other diameters, wall thickness, cover colours and pressure only on specific request.